

## FREEZE ALARM MONITORING SYSTEMS

<i>FreezeAlarm Model Comparison</i>			
Feature	Deluxe-FA-D & DX	Intermediate-FA-I	Basic-FA-B
Temperature Range Freeze Alarm will monitor	-50° to 199°F (-45° to 93°C)	-50° to 199°F (-45° to 93°C)	Pre-set at 45°F (7° C)
Calls you when power fails	Yes - immediate or with 1 hour delay	Yes - immediate or with 45 minute delay	No
Calls you when back-up battery needs replacing	Yes	Yes	No
Remotely program from any phone in the world	Yes - all functions	Yes - all functions	No
Remote check of current temp and power status	Yes	Yes	No
Remote Alarm Disabling	Yes	Yes	Yes
Remote switching of a relay to switch between two thermostats and warm up the place prior to arrival	Yes	No	No
Auxiliary monitoring of additional alarms such as our water alarm, a motion sensor, or other device.	Yes - purchase other devices separately	No	No
Monitor if it temperature falls too low, or if the temperature rises too high	Can monitor high & low temps at the same time	Can monitor either a high or low temperature	Set at 45°F (7° C)
Battery Backup	Yes - battery not included	Yes - battery not included	No-unit runs on 9V battery
High Resolution Voice Prompts and Messages	Yes	Yes	No
Custom Greeting Message	Yes	Yes	No
Custom Auxiliary Alarm Message	Yes	No	No
Alarm Format	Voice	Voice	Voice
Number of call-out telephone numbers	3	3	1
Temperature sensor type and length of cable (incl.)	External - 3' (.9m)	External - 3' (.9m)	
Security Code/Location ID	Yes - up to four digits	Yes - up to four digits	No
Selectable pulse or touch-tone™ dial-out	Yes	Yes	pulse / tone compatible
Ability to leave a number on a digital pager	Yes - DX model only	No	No