

CV300-4CH-001

User Friendly Web Ready DVR Security System with 4 Indoor/Outdoor Night Vision Surveillance Cameras

FEATURES

- Record over 2 years of video footage on the built-in 500GB hard drive
- View video online with no service fees from any computer in the world
- Transfer recorded footage directly to your computer using the included USB cable
- 4 indoor/outdoor weatherproof cameras are equipped with night vision for around the clock monitoring
- 24/7 lifetime live customer support is available through phone, email, and live web chat both before and after you buy

4 Channel DVR	
Functionality	Simplex
Video Compression	MPEG4
Number of cameras supported	4
Resolution	NTSC: 720 x 480 / PAL: 720 x 576
Recording Frame Rate	Max.60fps(adjustable)
Recording Time	over 2 years
Recording Resolution	NTSC: 720 x 240 / PAL: 720 x 288
Recording Qualities	low, normal, high, higher
Recording Modes	Motion Record, Continuous Record, Time Schedule Record
Recording Media	HDD
Storage Capacity	Max 500GB
Autostart Recording	Yes
Auto Resume Recording	Yes
HDD Type	Internal
Video Format	NTSC/PAL
Video Loss Alarm	Auto Detect Alarm
Video Inputs	4 CH Composite BNC
Video Display Output	1 CH Composite BNC (Monitor)
Live Frame Rate	120fps(adjustable)
Live Viewing	Full, Quad

Picture-in-Picture	No
Network Protocol	TCP/IP, DDNS, DHCP,
Network LAN IP	Static, Dynamic
Network Connection	10/100 BaseT Ethernet (RJ-45)
Back-up	Via USB cable to PC
Play Search Mode	Time/date, Event list
Play Speed	Yes
Pan/Tilt/Zoom	No
Play Mode	Full, Quad
OSD and System Menu Display	Yes
OSD Language Display	Six Language(English, French, German, Italian, Spanish, Portuguese)
Time and Date Stamp Display	Yes
Password Protection	Yes
Adjustable Screen Settings	Yes
File Transfer	USB2.0
Operating System	Linux
Disk Full Warning	Yes
Automatic Overwrite Option	Yes
Watermark	No
LED Indicators	Power, HDD
Housing Material	Iron
Housing Color	Black
Power Input	12V DC 3A
Power Consumption	13W~30W
Power Adapter Input	100V 50/60HZ~240 50/60HZ
Operating Temperature	(50â,~104â,%)
Operating Humidity	Under 90%

Dimensions	9.84 X 9.25 X 1.49 in
Weight	2.64 lbs
Other	
USB Port	Backup
Remote Control	Yes
Supported Peripherals	Remote Control, USB 2.0
Camera	
Image sensor	1/4" CMOS Color
Outdoor use	Yes
IP Rating	IP55
Resolution	400 TV Lines
Night Vision	Yes
Number of IR LEDs and Range	11, up to 20ft
IR LED control	Auto
Min. Illumination	0 lux
Battery Operable	No
Battery Life	No
Viewing Angle	65 Degrees
TV System	NTSC
Focal Length	6.0 mm
Focus Type	Fixed Focus
Connector	RCA
Microphone	No
Motion Detection	No
Audio Activation	No
Sun Shield	Yes
Housing Material	Metal
Housing Color	Platinum Silver

Electronic shutter speed	1/60 ~ 1/100,000 sec
Signal/Noise Ratio	>48dB
Power LED Indicator	No
Camera Bracket	Yes
Operating Temperature	-10° ~ 60° /Degrees
Operating Humidity	<95%
Camera Power Input	DC 12V 200mA
Power Adapter Input	AC 120V 60Hz
Dimensions	3.18i ¹ / ₄ Li ¹ / ₄ %oX 2.16(W)X 2.00(H) in
Weight	0.606 lbs