

SENSAPHONE Monitoring Sensor

WSG30 Wireless Sensors

WSG Wireless 4-20mA Sensor



Description

The WSG30 Wireless 4-20mA sensor is designed to work exclusively with the Sensaphone WSG30. This sensor includes a built-in radio transmitter, 4-20mA input and a 24V loop power supply. The sensor can be used to monitor the output of any 4-20mA transducer. The sensor comes with a plug-in power supply and three AA alkaline batteries which will power the sensor for several hours if main AC power fails.

Specifications

Operating Temperature Range:
32° to 122°F (0° to 50°C)

Operating Humidity Range:
0–95%

Input Load:
260 Ohms

Accuracy:
±1%

Transmit Power Output:
100mW (20dBm)

Range:
Up to 300' (90m)

Power Requirements:
(2) AA Batteries / 5VDC Power Supply (Included)

Wireless Technology:
ISM 2.4GHz, 100 mW (20dBm)

Housing:
White plastic

Size:
6.8" x 3.5" x 1.5"
17.2cm x 8.9cm x 3.8cm

Compatibility:
WSG30

**Specifications subject to change without notice*

Package Contents

- (1) WSG Wireless Dry Contact Sensor
- (2) AA Alkaline batteries
- (1) Mounting kit
- (1) 120VAC 60Hz/5VDC Power Supply

WSG Wireless 4-20mA Sensor FGD-WSG30-4-20